



Manufacturer of pneumatic impact tools and hydraulic tools for mines, quarries, construction industry, steelworks and foundries.

TECHNICKÉ ÚDAJE – TECHNISCHE DATEN – TECHNICAL DATA



SKK 9-D Pick Hammer

APPLICATION

Its design this tool is meant for integration with another machine. Operation of this tool is not permitted unless the complete unit of mounted machines conforms with the national Protection of Labour Regulations, especially in application of the Provision and Use of Work Equipment Regulations Directive.

Technické údaje – Technische data – Technical data	ISO	SKK 9-D
Hmotnost - Gewicht - Weight	kg	8,5
Energie úderu - Schlagenergie - Impact energy	J	26
Frekvence úderů - Schlagfrequenz - Impact frequency	Hz	28
Spotřeba vzduchu - Luftverbrauch - Air consumption	m ³ .min ⁻¹	1,1
Délka - Länge - Length	mm	380
Šířka - Breite - Width	mm	140
Provozní přetlak vzduchu - Betriebsluftdruck - Oper. air pressure	Bar / PSI	6,3 bar / 90 PSI
Stopka nástroje - Einsteckende - Shank	mm	Ø 20x60
Přívodní hadice - Luftzufuhrschlauch - Air supply hose	mm	Js 13
Připojení – Anschlussgewinde - Connecting thread		G 3/4"
Objednací číslo - Bestellnummer - Ordering code		9410-750

www.permon.cz
e-mail : prodej@permon.cz
e-mail : export@permon.cz

Roztoky 217, 270 23 Křivoklát, Česká republika
pro ČR, SR - for the Czech Rep. and SK
pro ostatní země - für andere Gebiete - for other territories
v :02.2025

T: + 420 313 521 548
T: + 420 313 521 563